



Technické parametre								
TYP	W	H	H <sub>2</sub>	d/D <sub>E</sub>	Z	m**	S**	a x a x h TYP
	m	m	m	mm	mm/m	kg	m <sup>2</sup>	m
S-100/8	1,0	10	0,75			103	4,7	0,3 x 0,3 x 1,5 F150/200
	1,5					104	4,8	
	2,0					105	4,9	
S-110	1,0	11	1,75	48; 60/195	12	107	5,0	
	1,5					109	5,1	
	2,0					110	5,2	
S-120	1,0	12	2,75			111	5,3	
	1,5					113	5,4	
	2,0					114	5,5	

Pevnostné parametre						
TYP	W	Hmotnosť svietidiel	Veterné oblasti podľa STN EN 1991-1-4:2008			M <sub>F</sub>
			Prípustná plocha svietidiel [m <sup>2</sup> ]			
	m	kg	I	II	III	kNm
<b>Jednoramenný výložník</b>						
<b>S-100/8</b>	2,0	15	0,77	0,46	0,25	18
<b>S-110</b>	2,0	15	0,63	0,33	0,14	18
<b>S-120</b>	2,0	15	0,46	0,19	-	18
<b>Dvojamenný výložník</b>						
<b>S-100/8</b>	2,0	15	0,7	0,39	0,1	18
<b>S-110</b>	2,0	15	0,54	0,24	-	18
<b>S-120</b>	2,0	15	0,37	0,1	-	18

\*\* - Parametre pre jednoramenné výložníky