


DKP...H100N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ

Available upon special order:
- cable ladders 2m long
- cable ladders 150, 250mm wide.

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKP100H100/3N	3000	100	498410	2	3,38	8200
DKP100H100/6N	6000	100	498510	2	3,38	8200
DKP200H100/3N	3000	200	498420	2	3,65	16400
DKP200H100/6N	6000	200	498520	2	3,65	16400
DKP300H100/3N	3000	300	498430	2	3,93	24600
DKP300H100/6N	6000	300	498530	2	3,93	24600
DKP400H100/3N	3000	400	498440	2	4,34	32800
DKP400H100/6N	6000	400	498540	2	4,34	32800
DKP500H100/3N	3000	500	498450	2	4,47	41000
DKP500H100/6N	6000	500	498550	2	4,47	41000
DKP600H100/3N	3000	600	498460	2	4,75	49200
DKP600H100/6N	6000	600	498560	2	4,75	49200

Connected products:

