


DUP...H100N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK

Available upon special order:
 - cable ladders 2m long
 - cable ladders 150, 250mm wide
 - production capability of perforated rungs

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUP100H100/3N	3000	100	499010	2	3,38	8200
DUP100H100/6N	6000	100	499110	2	3,38	8200
DUP200H100/3N	3000	200	499020	2	3,65	16400
DUP200H100/6N	6000	200	499120	2	3,65	16400
DUP300H100/3N	3000	300	499030	2	3,93	24600
DUP300H100/6N	6000	300	499130	2	3,93	24600
DUP400H100/3N	3000	400	499040	2	4,34	32800
DUP400H100/6N	6000	400	499140	2	4,34	32800
DUP500H100/3N	3000	500	499050	2	4,47	41000
DUP500H100/6N	6000	500	499150	2	4,47	41000
DUP600H100/3N	3000	600	499060	2	4,75	49200
DUP600H100/6N	6000	600	499160	2	4,75	49200

Connected products:

							
NO100N Protective Cap (Set)	LDCH100N Straight Connector	LKDCH100N Angle Connector	LDDCH100N Articulated Connector - Attachable	LDP...H100N 90° Horizontal Bend	LDZP...H100N 90° Horizontal Bend - External	TDP...H100N Horizontal Tee	CZDP...H100N Horizontal Cross-over
							
LPDWP...H100N 90° Vertical Bend - Internal	LPDZP...H100N 90° Vertical Bend - External	LPDP...H100N Adjustable Vertical Bend	RDSP...H100N Straight Reducer	RDL...H100N Left Reducer	RDPP...H100N Right Reducer		