


KKML...H42 45° Horizontal Bend

Overview:

Application
Diversions in cable routing.

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)



For installation use Screw Sets SGK M6×10 or SG M6×10.

Versions:

Sheet thickness: **0,7 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKML50H42	50	145905	20	0,08
KKML100H42	100	145910	20	0,13
KKML150H42	150	145915	10	0,22
KKML200H42	200	145920	10	0,31
KKML300H42	300	145930	10	0,59

Connected products:

							
KAJ...H42 Cable Tray	KGL...H42 Cable Tray	KGJ...H42 Cable Tray	KGR...H42 Cable Tray	KCJ...H42 Cable Tray	KCL...H42 Cable Tray	KOL...H42 Cable Tray	KOJ...H42 Cable Tray
							
KBR...H42 Cable Tray	KBJ...H42 Cable Tray	OPZJ...H42 Horizontal Bypass	OPZBJ...H42 Horizontal Bypass	OPNJ...H42 Vertical Bypass	OPNBj...H42 Vertical Bypass	LUJ...H42 90° Vertical Bend	LUBJ...H42 90° Vertical Bend
							
LUMJ...H42 45° Vertical Bend	LUMBJ...H42 45° Vertical Bend	LUPJ...H42 90° Vertical Bend	LUMPJ...H42 45° Vertical Bend	TRSJ...H42 Vertical Tee - Crosswise	TRSBj...H42 Vertical Tee - Crosswise	SG... Screw Set	SM... Screw Set