PZDDC... Cover

Overview:

Application
Protecting cables against damage. Tight cover protection against accumulation of dirt and dust.

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

Cover with a lock.
BENEFITS: - thanks to specially-shaped profile additional regulation
in width is obtained, particularly useful when hot-dip galvanised.
IMPORTANT!
FOR 100mm WIDTH - 1 LOCK – SYMMETRICALLY
COVER 2000mm LONG CONTAINS 2 LOCKS
COVER 3000mm LONG CONTAINS 3 LOCKS
FOR 200-600mm WIDTHS- 2 LOCKS – IN A ROW
COVER 2000mm LONG CONTAINS 4 LOCKS
COVER 3000mm LONG CONTAINS 6 LOCKS

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
PZDDC100/3	3000	104	402310	10	1,97
PZDDC200/3	3000	204	402320	6	3,62
PZDDC300/3	3000	304	402330	6	5,27
PZDDC400/3	3000	404	402340	4	6,92
PZDDC500/3	3000	504	402350	4	8,56
PZDDC600/3	3000	604	402360	4	10,21