

## KKNMd 45° Horizontal Bend 2 Comp.

### Overview:

**Application**

Diversion in cable routing



**Material**

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**

**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

**E-** stainless steel (SS)




### Versions:


Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
<b>KKNMd 175H48</b>	<b>175</b>	<b>541117</b>	<b>4</b>	<b>0,76</b>
<b>KKNMd 190H48</b>	<b>190</b>	<b>541119</b>	<b>4</b>	<b>0,84</b>
<b>KKNMd 240H48</b>	<b>240</b>	<b>541124</b>	<b>4</b>	<b>1,04</b>
<b>KKNMd 340H48</b>	<b>340</b>	<b>541134</b>	<b>4</b>	<b>1,58</b>

### Connected products:



KN Underfloor Trunking



KNd Underfloor Trunking 2 Comp.



KNt Underfloor Trunking 3 Comp.



KKN 90° Horizontal Bend




KKNd 90° Horizontal Bend 2 Comp.



KKNt 90° Horizontal Bend 3 Comp.



KKNM 45° Horizontal Bend



KKNMt 45° Horizontal Bend 3 Comp.



TKN Horizontal Tee



CZKN Horizontal Cross-over



LK Vertical Bend



LKd Vertical Bend 2 Comp.



LKt Vertical Bend 3 Comp.



RKN Straight Reducer



RKNd Straight Reducer 2 Comp.



RKNt Straight Reducer 3 Comp.