# CWP40H35... Support Channel

# **Overview:**

## Application

Used for suspending lighting, and as construction element for installing cable trays, and ladders. Used as an element for supporting Brackets WW, WWS, WWD, WWC, WWCN, WPL, WTL, WPT, WWT, WMC, and WMCN.

#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)


### Available to order:

Sheet thickness: 1,5 mm

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG) E- stainless steel sections to 3m long (SS) L- powder coating in a full range of colours (PC)

Important! In case of large quantity orders services available are any sections up to 6m long

Versions:



As a constant

Connected products:

401135/2	2000		·	010510	U	33	2,32
CWP40H35/3	3000	40	)	610530	8	35	3,48
		Succession of the local division of the loca	55555	a dia	5 pl		12000
CWZP30H20 Support Channe	CWZP40H22 elSupport Channe	CWZP40H47 <sup>el</sup> Support Channe	PLP Perf Steel Strip	forated PTP20 Perforate Band	PZC Asse d Steel Plate	mbly NO40x20 Protective Cap	LCW40H35 Channel Connector
			1	-			and the second
LCW40H47 Channel Connector	LCM50H30 Channel Connector	NO40x47 Protective Cap	CP28H12. Channel	CP40H20 Channel	LC40H20 Channel Connector	CMP40H22 Support Chan	KTP25H25 <sup>nel</sup> Angle Profile
S. S	1		Social States	68 4'D'O		т50	O
KTP35H35 Angle Profile	NOK Protective Cap	NO80x37 Protective Cap	CWP30H3 Support C	0 LCW30H3 hannel Connecto	Channel	Galvanised St Tape	<sup>eel</sup> DSO Galvanised Stee Wire
					Ø	10000	10000

NO30x30

NO40x40N NO40x60 Protective Cap Protective Cap Protective Cap

DPH... I-Beam

NO40x30 NO50x30 Protective Cap Protective Cap

LCM40H60 Channel

Connector

LCM50H50 Channel Connector

