

CWC40H22... Support Channel

Overview:

Application

Used for suspending lighting, and as construction element for installing cable trays, and ladders. Used as an element for supporting Brackets WW, WWS, WS, WSZ, WZS, WWC, WWCN, WMC, WMCN, WPL, WWD, and WPT.

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)

Important! In case of large quantity orders available for any sections up to 6m long and for channel made of steel sheet 2.5mm thick. For the assembly of support channel in combination with channel connector - use Screw Sets SGK M10x20 or SG M10x20.



Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Height H [mm]	Weight 1 pc.
CWC40H22/2	2000	40	610320	8	22	2,68
CWC40H22/3	3000	40	610330	8	22	4,02
CWC40H22/6	6000	40	610360	8	22	8,04

Connected products:



PZC... Assembly Plate



NO40x20 Protective Cap



NO40x47 Protective Cap



NOK... Protective Cap



NO80x37 Protective Cap



TSO... Galvanised Steel Tape



DSO... Galvanised Steel Wire



NO30x30 Protective Cap



NO40x40N Protective Cap



NO40x60 Protective Cap



DPH... I-Beam



NO40x30 Protective Cap



NO50x30 Protective Cap