

SZP35H7... DIN Rail

Overview:

Application

For installing all types of DIN Rail-mounted AC circuit breakers (RDs/RCDs/SPDs, GFCIs, etc.), contactors, relays


Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
L- powder coating in a full range of colours (PC)

Production capacity of manufacturing any sections up to 6m long.



Versions:

Sheet thickness: **1,0 mm**

| Symbol | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Height H [mm] | Weight 1 pc. |
|-------------|--------------|--------------|------------------|-----------------|---------------|--------------|
| SZP35H7/02 | 200 | 35 | 613102 | 50 | 7 | 0,06 |
| SZP35H7/03 | 300 | 35 | 613103 | 50 | 7 | 0,09 |
| SZP35H7/04 | 400 | 35 | 613104 | 50 | 7 | 0,12 |
| SZP35H7/05 | 500 | 35 | 613105 | 50 | 7 | 0,15 |
| SZP35H7/095 | 950 | 35 | 613195 | 50 | 7 | 0,28 |
| SZP35H7/1 | 1000 | 35 | 613110 | 50 | 7 | 0,30 |
| SZP35H7/2 | 2000 | 35 | 613120 | 30 | 7 | 0,60 |
| SZP35H7/3 | 3000 | 35 | 613130 | 30 | 7 | 0,90 |

Connected products:

