

## SZP35H7... DIN Rail

### Overview:

#### Application

For installing all types of DIN Rail-mounted AC circuit breakers (RDs/RCDs/SPDs, GFCIs, etc.), contactors, relays


#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**L-** powder coating in a full range of colours (PC)

**Production capacity of manufacturing any sections up to 6m long.**



### Versions:

Sheet thickness: **1,0 mm**

| Symbol             | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Height H [mm] | Weight 1 pc. |
|--------------------|--------------|--------------|------------------|-----------------|---------------|--------------|
| <b>SZP35H7/02</b>  | <b>200</b>   | <b>35</b>    | <b>613102</b>    | <b>50</b>       | <b>7</b>      | <b>0,06</b>  |
| <b>SZP35H7/03</b>  | <b>300</b>   | <b>35</b>    | <b>613103</b>    | <b>50</b>       | <b>7</b>      | <b>0,09</b>  |
| <b>SZP35H7/04</b>  | <b>400</b>   | <b>35</b>    | <b>613104</b>    | <b>50</b>       | <b>7</b>      | <b>0,12</b>  |
| <b>SZP35H7/05</b>  | <b>500</b>   | <b>35</b>    | <b>613105</b>    | <b>50</b>       | <b>7</b>      | <b>0,15</b>  |
| <b>SZP35H7/095</b> | <b>950</b>   | <b>35</b>    | <b>613195</b>    | <b>50</b>       | <b>7</b>      | <b>0,28</b>  |
| <b>SZP35H7/1</b>   | <b>1000</b>  | <b>35</b>    | <b>613110</b>    | <b>50</b>       | <b>7</b>      | <b>0,30</b>  |
| <b>SZP35H7/2</b>   | <b>2000</b>  | <b>35</b>    | <b>613120</b>    | <b>30</b>       | <b>7</b>      | <b>0,60</b>  |
| <b>SZP35H7/3</b>   | <b>3000</b>  | <b>35</b>    | <b>613130</b>    | <b>30</b>       | <b>7</b>      | <b>0,90</b>  |

### Connected products:

