

SZP35H15... DIN Rail

Overview:

Application

For installing all types of DIN Rail-mounted AC circuit breakers (RDs/RCDs/SPDs, GFCIs, etc.), contactors, relays


Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
L- powder coating in a full range of colours (PC)

Production capacity of manufacturing any sections up to 6m long.



Versions:

Sheet thickness: **1,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Height H [mm]	Weight 1 pc.
SZP35H15/02	200	35	613202	50	15	0,08
SZP35H15/03	300	35	613203	50	15	0,12
SZP35H15/04	400	35	613204	50	15	0,16
SZP35H15/05	500	35	613205	50	15	0,20
SZP35H15/095	950	35	613295	50	15	0,38
SZP35H15/1	1000	35	613210	50	15	0,40
SZP35H15/2	2000	35	613220	30	15	0,80
SZP35H15/3	3000	35	613230	30	15	1,20

Connected products:

CWZJ30H20... Support Channel	PCWZJ... Cover For Channel	PTJ... Perforated Steel Band	PZC... Assembly Plate	NO40x20 Protective Cap	NO40x47 Protective Cap	NOK... Protective Cap	NO80x37 Protective Cap
SZB35H7... DIN Rail	SZB35H15... DIN Rail	TSO... Galvanised Steel Tape	DSO... Galvanised Steel Wire	SZP35H7... DIN Rail	LCW20H10 Channel Connector	NO30x30 Protective Cap	NO40x40N Protective Cap
NO40x60 Protective Cap	DPH... I-Beam	NO40x30 Protective Cap	NO50x30 Protective Cap				