


WPCW/WPCO... Ceiling Bracket

Overview:

Application
Suspending cable routes.

Material
Steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

Available to order:
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)



FEATURES & BENEFITS:
Improved mechanical properties
Self-drain holes of both types of
brackets - bolted - and snap-in type
Identical internal surfaces of the channel allow for
bracket installation from each side

Versions:

Symbol	Length L [m]	Catalogue number	Quantity in box	Weight 1 pc.
WPCW/WPCO200	200	750620	20	0,90
WPCW/WPCO300	300	750630	20	1,10
WPCW/WPCO400	400	750640	10	1,30
WPCW/WPCO500	500	750650	10	1,47
WPCW/WPCO600	600	750660	10	1,67
WPCW/WPCO700	700	750670	10	1,86
WPCW/WPCO800	800	750680	10	2,10
WPCW/WPCO900	900	750690	10	2,25
WPCW/WPCO1000	1000	750611	10	2,45
WPCW/WPCO2000	2000	750612	4	4,40
WPCW/WPCO3000	3000	750613	4	6,35
WPCW4000	4000	750641	4	8,25
WPCW5000	5000	750651	4	10,12
WPCW6000	6000	750661	4	12,10