


BR.../1 Spacer

Overview:

Application

Used as spacer protecting against crushing steel profile during installation.

Used with channel and Z-Profile .



SYMBOL BLAZHO ROZPOČTOVÉ	DUBOR	
	PRÍSLUŠIE DO	
	CELOVNÁ	WSPORNÁ
BR33/1 BR33/2	CMT40H40, CMT40H60, CMT40H80	
BR34/1 BR34/2	CMT41H41	
BR35/1 BR35/2	CWC40H40, CMM41H41, CPMC41H82, CMMC40H40, CMC40H60	WPCE/WPCE...
BR36/1 BR36/2	CMC41H41, CWP40H40, CMPC41H82, CMMP40H40, CMP40H60	
BR37/1 BR37/2	CMP41H41	
BR45/1 BR45/2	CC50H35	WPCE...
BR48/1 BR48/2	CT55H50	WPCT...
BR50/1 BR50/2	CC55H50	
BR51/1 BR51/2	CE60H40	WPSE...
BR53/1 BR53/2	CT60H40	WPST...
BR61/1 BR61/2	CE70H50	WPCE/WPCE...
BR63/1 BR63/2	CT70H50	

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

WE RECOMMEND USING SPACERS BR... WHEN SCREWING UP HEAD PLATES WITH STEEL PROFILES. SPACER BR... PROTECTS AGAINST CRUSHING CHANNEL OR Z - PROFILES DURING INSTALLATION.

Versions:

Symbol	Width a [mm]	Catalogue number	Quantity in box	Application	Vhodné pre
BR33/1	33	704011	50	CWT40H40, CWT40H60, CWT40H80, CMT40H60, CMT40H80	
BR34/1	34	704141	50	CMT41H41	
BR35/1	35	704131	50	CWC40H40, CMM41H41, CPMC41H82, CMMC40H40, CMC40H60	WPCW/WPCO...
BR36/1	36	704121	50	CMC41H41, CWP40H40, CMPC41H82, CMMP40H40, CMP40H60	
BR37/1	37	704111	50	CMP41H41	
BR45/1	45	704145	50	CC50H35	WPCB...
BR48/1	48	705521	50	CT55H50	WPCT...
BR50/1	50	705511	50	CC55H50	
BR51/1	51	705911	50	CE60H40	WPSE...
BR53/1	53	706021	50	CT60H40	WPST...
BR61/1	61	707021	50	CE70H50	WPCE/WPCEO...
BR63/1	63	707011	50	CT70H50	