


## DGOP...H60N Cable Ladder

### Overview:

**APPLICATION**  
Cable routing

**MATERIAL**  
Steel, strip-galv. acc. to the  
Sendzimir method PN-EN 10346:2011  
Available finishes:  
L- powder coating in a full range of colours (PC)



- For assembly use 2 pcs of Straight connectors LDC/LDOCH60 and 8 sets of screw SGKM8x14
- For vertical direction change use 2 pcs of Articulated Connector LGC/LGOCH60 and 8 sets of screw SGKM8x14
- For horizontal direction change use 2 pcs of Angle Connector LKD/LKDOCH60 and 8 sets of screw SGKM8x14

**Max. safe load: 20 kg/m**  
**Max. spacing of supports: 1.5m**

### Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DGOP100H60/3N	3000	100	863013	2	2,67
DGOP100H60/6N	6000	100	863010	2	2,67
DGOP200H60/3N	3000	200	863023	2	3,39
DGOP200H60/6N	6000	200	863020	2	3,39
DGOP300H60/3N	3000	300	863033	2	3,72
DGOP300H60/6N	6000	300	863030	2	3,72
DGOP400H60/3N	3000	400	863043	2	4,38
DGOP400H60/6N	6000	400	863040	2	4,38
DGOP500H60/3N	3000	500	863053	2	4,51
DGOP500H60/6N	6000	500	863050	2	4,51
DGOP600H60/3N	3000	600	863063	2	4,99
DGOP600H60/6N	6000	600	863060	2	4,99

### Connected products:

