


## DUP...H120N Cable Ladder

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
E- stainless steel sections to 3m long (SS)  
L- powder coating in a full range of colours (PC)



**NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK**

**Available upon special order:**

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

### Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
<b>DUP100H120/3N</b>	3000	100	<b>473010</b>	2	<b>3,86</b>	<b>8400</b>
<b>DUP100H120/6N</b>	6000	100	<b>473110</b>	2	<b>3,86</b>	<b>8400</b>
<b>DUP200H120/3N</b>	3000	200	<b>473020</b>	2	<b>4,11</b>	<b>18400</b>
<b>DUP200H120/6N</b>	6000	200	<b>473120</b>	2	<b>4,11</b>	<b>18400</b>
<b>DUP300H120/3N</b>	3000	300	<b>473030</b>	2	<b>4,41</b>	<b>28600</b>
<b>DUP300H120/6N</b>	6000	300	<b>473130</b>	2	<b>4,41</b>	<b>28600</b>
<b>DUP400H120/3N</b>	3000	400	<b>473040</b>	2	<b>4,82</b>	<b>38800</b>
<b>DUP400H120/6N</b>	6000	400	<b>473140</b>	2	<b>4,82</b>	<b>38800</b>
<b>DUP500H120/3N</b>	3000	500	<b>473050</b>	2	<b>4,96</b>	<b>49000</b>
<b>DUP500H120/6N</b>	6000	500	<b>473150</b>	2	<b>4,96</b>	<b>49000</b>
<b>DUP600H120/3N</b>	3000	600	<b>473060</b>	2	<b>5,23</b>	<b>59200</b>
<b>DUP600H120/6N</b>	6000	600	<b>473160</b>	2	<b>5,23</b>	<b>59200</b>