


DUC...H120N Cable Ladder

Overview:

- Application**
 Cable routing
- Material**
 Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)
- Available to order:**
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK

Available upon special order:

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

Versions:

Sheet thickness: 2,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUC100H120/3N	3000	100	473210	2	4,98	8400
DUC100H120/6N	6000	100	473310	2	4,98	8400
DUC200H120/3N	3000	200	473220	2	5,51	18400
DUC200H120/6N	6000	200	473320	2	5,51	18400
DUC300H120/3N	3000	300	473230	2	5,88	28600
DUC300H120/6N	6000	300	473330	2	5,88	28600
DUC400H120/3N	3000	400	473240	2	6,42	38800
DUC400H120/6N	6000	400	473340	2	6,42	38800
DUC500H120/3N	3000	500	473250	2	6,61	49000
DUC500H120/6N	6000	500	473350	2	6,61	49000
DUC600H120/3N	3000	600	473260	2	6,96	59200
DUC600H120/6N	6000	600	473360	2	6,96	59200