


LLL...H30 Adjustable Vertical Bend

Overview:

Application
 Diversions in cable routing. Full-range angle adjustment with a lock.

Material
 Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)



For installation use Screw Sets SGK M6×10 or SG M6×10.
Adjustable Vertical Bend is delivered fully assembled together with:
2 Adjustable Vertical Bend Elements
4 pairs of Angle Connectors
6 sets of screws

Versions:

Sheet thickness: **0,7 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
LLL50H30	50	132305	2	0,45
LLL100H30	100	132310	2	0,57
LLL150H30	150	132315	2	0,65
LLL200H30	200	132320	2	0,83
LLL300H30	300	132330	2	1,07

Connected products:

							
KGR...H30 Cable Tray	KGL...H30 Cable Tray	KGJ...H30 Cable Tray	KBJ...H30 Cable Tray	KBR...H30 Cable Tray	KBL...H30 Cable Tray	LPLH30 Straight Connector	LPPH30 Straight Connector
							
LPMH30 Straight Connector	LPMLH30 Straight Connector	ELJ...H30 Adjustable Vertical Bend Element	ELL...H30 Adjustable Vertical Bend Element	ELBJ...H30 Adjustable Vertical Bend Element	ELBL...H30 Adjustable Vertical Bend Element	SGK... Screw Set	SM... Screw Set