


DGOD...H60N Cable Ladder

Overview:

APPLICATION
Cable routing

MATERIAL
Steel, strip-galv. acc. to the
Sendzimir method PN-EN 10346:2011
Available finishes:
L- powder coating in a full range of colours (PC)



- For assembly use 2 pcs of Straight connectors
LDC/LDOCH60
and 8 sets of screw SGK8x14
- For vertical direction change use 2 pcs of Articulated
Connector
LGC/LGOCH60 and 8 sets of screw SGK8x14
- For horizontal direction change use 2 pcs of Angle
Connector
LKD/LKDOCH60 and 8 sets of screw SGK8x14

Max. safe load: 20 kg/m
Max. spacing of supports: 1.5m

Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DGOD100H60/3N	3000	100	867010	2	2,01
DGOD100H60/6N	6000	100	867110	2	2,01
DGOD200H60/3N	3000	200	867020	2	2,24
DGOD200H60/6N	6000	200	867120	2	2,24
DGOD300H60/3N	3000	300	867030	2	2,47
DGOD300H60/6N	6000	300	867130	2	2,47
DGOD400H60/3N	3000	400	867040	2	2,81
DGOD400H60/6N	6000	400	867140	2	2,81

Connected products:

