


KBD...H50 Cable Tray

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)




Important!
Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBP... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile). Available when ordering in large quantity are 6m long tray sections.
To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBD50H50/3	3000	50	152405	12	1,80	2300
KBD100H50/3	3000	100	152410	6	2,30	4800
KBD150H50/3	3000	150	152415	6	2,80	7300
KBD200H50/3	3000	200	152420	6	3,30	9800
KBD300H50/3	3000	300	152430	4	4,30	14800
KBD400H50/3	3000	400	151840	4	5,30	19800
KBD500H50/3	3000	500	151850	2	6,30	24800
KBD600H50/3	3000	600	151860	2	7,30	29800

Connected products:



KRPJ...H50 Vertical Elbow - Right	KRPBJ...H50 Vertical Elbow - Right	KRLJ...H50 Vertical Elbow - Left	KRLBJ...H50 Vertical Elbow - Left	TRJ...H50 Vertical Tee -Lengthwise	TRBJ...H50 Vertical Tee -Lengthwise	TRSJ...H50 Vertical Tee - Crosswise	TRSBJ...H50 Vertical Tee - Crosswise
							
RKLJ...H50 Left Reducer	RKLBJ...H50 Left Reducer	RKPJ...H50 Right Reducer	RKPBJ...H50 Right Reducer	RKSJ...H50 Straight Reducer	RKSBJ...H50 Straight Reducer	LRJH50 Corner Connector	LRBJH50 Corner Connector
							
TKDJ...H50 Add-on Tee	LRPJH50 Corner Connector						