

## KCD...H110N Cable Tray

### Overview:


**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
E- stainless steel (SS)  
L- powder coating in a full range of colours (PC)

**Important! Possibility of joining cable tray sections together through sliding one into another and connectorfree assembly.**

**Available when ordering in large quantity are 2m and 6m long tray sections. To install cable tray use Screw Sets SGK M6x12 or SG M6x12.**



### Versions:

Sheet thickness: 1,2 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KCD100H110/3N	3000	100	120610	4	2,92	10800
KCD150H110/3N	3000	150	120615	4	3,34	16300
KCD200H110/3N	3000	200	120620	4	3,75	21800
KCD300H110/3N	3000	300	120630	2	4,58	32800
KCD400H110/3N	3000	400	120640	2	5,41	43800
KCD500H110/3N	3000	500	120650	2	6,24	54800
KCD600H110/3N	3000	600	120660	2	7,07	65800