

KCP...H110N Cable Tray

Overview:

Application
Cable routing

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)


E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

Important! Joining cable tray sections together only through

the use of connectors (lack of cut in the flange at the end of side profile).

Available when ordering in large quantity are 2m and 6m long tray sections. To install cable tray use Screw Sets SGK M6x12 or SG M6x12.



Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KCP100H110/3N	3000	100	120810	4	3,52	10800
KCP100H110/6N	6000	100	120811	4	3,52	10800
KCP150H110/3N	3000	150	120815	4	4,02	16300
KCP150H110/6N	6000	150	120816	4	4,02	16300
KCP200H110/3N	3000	200	120820	2	4,52	21800
KCP200H110/6N	6000	200	120821	2	4,52	21800
KCP300H110/3N	3000	300	120830	2	5,51	32800
KCP300H110/6N	6000	300	120831	2	5,51	32800
KCP400H110/3N	3000	400	120840	2	6,51	43800
KCP400H110/6N	6000	400	120841	2	6,51	43800
KCP500H110/3N	3000	500	120850	2	7,51	54800
KCP500H110/6N	6000	500	120851	2	7,51	54800
KCP600H110/3N	3000	600	120860	2	8,51	65800
KCP600H110/6N	6000	600	120861	2	8,51	65800