


## KBD...H110 Cable Tray

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
E- stainless steel (SS)  
L- powder coating in a full range of colours (PC)



**Important!**  
**Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBP... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile).**  
**Available when ordering in large quantity are 6m long tray sections.**  
**To install cable tray use Screw Sets SGK M6x12 or SG M6x12.**

### Versions:

Sheet thickness: 1,2 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBD100H110/3	3000	100	121810	4	3,59	10800
KBD150H110/3	3000	150	121815	4	3,99	16300
KBD200H110/3	3000	200	121820	4	4,49	21800
KBD300H110/3	3000	300	121830	2	5,49	32800
KBD400H110/3	3000	400	121840	2	6,49	43800
KBD500H110/3	3000	500	121850	2	7,49	54800
KBD600H110/3	3000	600	121860	2	8,49	65800