


DUP/DUOP...H60 Cable Ladder

Overview:

APPLICATION
Cable routing

MATERIAL
Steel, strip-galv. acc. to the
Sendzimir method PN-EN 10346:2011
Available finishes:
L- powder coating in a full range of colours (PC)



- For assembly use 2 pcs of Straight connectors LDC/LDOCH60 and 8 sets of screw SGKM8x14
- For vertical direction change use 2 pcs of Articulated Connector LGC/LGOCH60 and 8 sets of screw SGKM8x14
- For horizontal direction change use 2 pcs of Angle Connector LKD/LKDOCH60 and 8 sets of screw SGKM8x14

Max. safe load: 20 kg/m
Max. spacing of supports: 1.5m

Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DUP/DUOP100H60 /3	3000	100	466310	2	2,41
DUP/DUOP100H60 /6	6000	100	466410	2	2,41
DUP/DUOP200H60 /3	3000	200	466320	2	2,69
DUP/DUOP200H60 /6	6000	200	466420	2	2,69
DUP/DUOP300H60 /3	3000	300	466330	2	2,97
DUP/DUOP300H60 /6	6000	300	466430	2	2,97
DUP/DUOP400H60 /3	3000	400	466340	2	3,38
DUP/DUOP400H60 /6	6000	400	466440	2	3,38