

KAP...H60 Cable Tray

Overview:

Application
Cable routing



Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

Important! Joining cable tray sections together only through the use of connectors (lack of cut in the flange at the end of side profile). To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

Benefits of the New System:
- large perforation in the tray side: of size 24 × 65mm, and in the bottom, sized 34 × 65mm, allow cable bundles to be pulled out from anywhere within the tray without the need to use any fittings
- dense perforation for excellent heat transfer, designed to enable cable tray installation on supports from BAKS anywhere within the system
- rounded tray flange edges with longitudinal ribbing allow the covers to snap firmly into place

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KAP50H60/3	3000	50	171515	12	2,09	2900
KAP100H60/3	3000	100	171516	12	2,37	5800
KAP150H60/3	3000	150	171616	6	2,88	8800
KAP200H60/3	3000	200	171716	6	3,32	11800
KAP300H60/3	3000	300	171816	6	4,31	17800
KAP400H60/3	3000	400	171916	4	5,31	23800
KAP500H60/3	3000	500	172016	2	6,29	29800
KAP600H60/3	3000	600	172116	2	7,26	35800