



KSP...H110 Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile
- cable tray from 2 up to 12m long
- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSP200H110/3	3000	200	230021	2	6,05	21700
KSP200H110/6	6000	200	230020	2	6,05	21700
KSP300H110/3	3000	300	230031	2	6,95	32700
KSP300H110/6	6000	300	230030	2	6,95	32700
KSP400H110/3	3000	400	230041	2	7,85	43700
KSP400H110/6	6000	400	230040	2	7,85	43700
KSP500H110/3	3000	500	230051	2	8,75	54700
KSP500H110/6	6000	500	230050	2	8,75	54700
KSP600H110/3	3000	600	230061	2	9,65	65700
KSP600H110/6	6000	600	230060	2	9,65	65700