



KSC...H110 Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile
- cable tray from 2 up to 12m long
- cable tray: 1,2 and 2,5mm thick sheet.
Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: 2,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSC200H110/3	3000	200	230121	2	7,56	21700
KSC200H110/6	6000	200	230120	2	7,56	21700
KSC300H110/3	3000	300	230131	2	8,56	32700
KSC300H110/6	6000	300	230130	2	8,56	32700
KSC400H110/3	3000	400	230141	2	9,36	43700
KSC400H110/6	6000	400	230140	2	9,36	43700
KSC500H110/3	3000	500	230151	2	10,26	54700
KSC500H110/6	6000	500	230150	2	10,26	54700
KSC600H110/3	3000	600	230161	2	11,16	65700
KSC600H110/6	6000	600	230160	2	11,16	65700