

LZKSC...H110 90° Vertical Bend - External

Overview:

Application

Diversion in cable routing

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)


L- powder coating in a full range of colours (PC)

For joining fittings to cable tray use Straight Connectors for Fittings

LSSU... and Screw Sets SGKM8×16. Capability of creating vertical bends of any internal radius adjusted to minimum cable bending angle.

FEATURES & BENEFITS:

- eye-pleasing appearance
- high mechanical properties
- even distribution of cables
- optional use of covers



Versions:

Sheet thickness: **2,0 mm**

| Symbol | Width a [mm] | Catalogue number | Quantity in box | Weight 1 pc. |
|--------------|--------------|------------------|-----------------|--------------|
| LZKSC200H110 | 200 | 231222 | 2 | 7,35 |
| LZKSC300H110 | 300 | 231232 | 2 | 8,36 |
| LZKSC400H110 | 400 | 231242 | 2 | 9,18 |
| LZKSC500H110 | 500 | 231252 | 2 | 10,45 |
| LZKSC600H110 | 600 | 231262 | 2 | 11,59 |