



KSP...H120 Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile
- cable tray from 2 up to 12m long
- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: **UKZ1**, **UKZ2**

Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSP200H120/3	3000	200	240020	2	7,04	22600
KSP200H120/6	6000	200	240021	2	7,04	22600
KSP300H120/3	3000	300	240030	2	8,00	34600
KSP300H120/6	6000	300	240031	2	8,00	34600
KSP400H120/3	3000	400	240040	2	8,96	46600
KSP400H120/6	6000	400	240041	2	8,96	46600
KSP500H120/3	3000	500	240050	2	9,92	58600
KSP500H120/6	6000	500	240051	2	9,92	58600
KSP600H120/3	3000	600	240060	2	10,88	70600
KSP600H120/6	6000	600	240061	2	10,88	70600