



KSC...H120 Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile
- cable tray from 2 up to 12m long
- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: 2,0 mm

| Symbol | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Weight [1m] | Effective section |
|--------------|--------------|--------------|------------------|-----------------|-------------|-------------------|
| KSC200H120/3 | 3000 | 200 | 240120 | 2 | 8,46 | 22600 |
| KSC200H120/6 | 6000 | 200 | 240121 | 2 | 8,46 | 22600 |
| KSC300H120/3 | 3000 | 300 | 240130 | 2 | 9,36 | 34600 |
| KSC300H120/6 | 6000 | 300 | 240131 | 2 | 9,36 | 34600 |
| KSC400H120/3 | 3000 | 400 | 240140 | 2 | 10,26 | 46600 |
| KSC400H120/6 | 6000 | 400 | 240141 | 2 | 10,26 | 46600 |
| KSC500H120/3 | 3000 | 500 | 240150 | 2 | 11,16 | 58600 |
| KSC500H120/6 | 6000 | 500 | 240151 | 2 | 11,16 | 58600 |
| KSC600H120/3 | 3000 | 600 | 240160 | 2 | 12,06 | 70600 |
| KSC600H120/6 | 6000 | 600 | 240161 | 2 | 12,06 | 70600 |