

DSP...H100 Cable Ladder

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
 - cable ladder from 2 to 12m long
 - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps UK

Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSP200H100/3	3000	200	410020	2	4,74	16400
DSP200H100/6	6000	200	410021	2	4,74	16400
DSP300H100/3	3000	300	410030	2	5,02	24600
DSP300H100/6	6000	300	410031	2	5,02	24600
DSP400H100/3	3000	400	410040	2	5,31	32800
DSP400H100/6	6000	400	410041	2	5,31	32800
DSP500H100/3	3000	500	410050	2	5,60	41000
DSP500H100/6	6000	500	410051	2	5,60	41000
DSP600H100/3	3000	600	410060	2	5,89	49200
DSP600H100/6	6000	600	410061	2	5,89	49200