


## DSC...H100 Cable Ladder

### Overview:

#### Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E**- stainless steel (SS)  
**L**- powder coating in a full range of colours (PC)

#### IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
  - cable ladder from 2 to 12m long
  - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps  
**UK**

### Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSC200H100/3	3000	200	410123	2	5,75	16400
DSC200H100/6	6000	200	410226	2	5,75	16400
DSC300H100/3	3000	300	410133	2	5,89	24600
DSC300H100/6	6000	300	410236	2	5,89	24600
DSC400H100/3	3000	400	410143	2	6,38	32800
DSC400H100/6	6000	400	410246	2	6,38	32800
DSC500H100/3	3000	500	410153	2	6,66	41000
DSC500H100/6	6000	500	410256	2	6,66	41000
DSC600H100/3	3000	600	410163	2	6,91	49200
DSC600H100/6	6000	600	410266	2	6,91	49200