


## DSC...H110 Cable Ladder

### Overview:

#### Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E**- stainless steel (SS)  
**L**- powder coating in a full range of colours (PC)

#### IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
  - cable ladder from 2 to 12m long
  - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps  
**UK**

### Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSC200H110/3	3000	200	411723	2	6,05	17400
DSC200H110/6	6000	200	411826	2	6,05	17400
DSC300H110/3	3000	300	411733	2	6,19	26600
DSC300H110/6	6000	300	411836	2	6,19	26600
DSC400H110/3	3000	400	411743	2	6,68	35800
DSC400H110/6	6000	400	411846	2	6,68	35800
DSC500H110/3	3000	500	411753	2	6,96	45000
DSC500H110/6	6000	500	411856	2	6,96	45000
DSC600H110/3	3000	600	411763	2	7,21	54200
DSC600H110/6	6000	600	411866	2	7,21	54200