


DSC...H110 Cable Ladder

Overview:

Application
 Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.

Material
 Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)



IMPORTANT!
 In case of large quantity orders available are:
 - cable ladders with slotted side walls
 - cable ladder from 2 to 12m long
 - cable ladders of 1.2, 2.5mm steel thickness of a side wall
 Cable ladder with rungs adapted for use with Cable Clamps UK

Versions:

Sheet thickness: 2,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSC200H110/3	3000	200	411723	2	6,05	17400
DSC200H110/6	6000	200	411826	2	6,05	17400
DSC300H110/3	3000	300	411733	2	6,19	26600
DSC300H110/6	6000	300	411836	2	6,19	26600
DSC400H110/3	3000	400	411743	2	6,68	35800
DSC400H110/6	6000	400	411846	2	6,68	35800
DSC500H110/3	3000	500	411753	2	6,96	45000
DSC500H110/6	6000	500	411856	2	6,96	45000
DSC600H110/3	3000	600	411763	2	7,21	54200
DSC600H110/6	6000	600	411866	2	7,21	54200