

DSC...H120 Cable Ladder

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
 - cable ladder from 2 to 12m long
 - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps UK

Versions:

Sheet thickness: 2,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSC200H120/3	3000	200	430120	2	6,95	22600
DSC200H120/6	6000	200	430220	2	6,95	22600
DSC300H120/3	3000	300	430130	2	7,09	34600
DSC300H120/6	6000	300	430230	2	7,09	34600
DSC400H120/3	3000	400	430140	2	7,58	46600
DSC400H120/6	6000	400	430240	2	7,58	46600
DSC500H120/3	3000	500	430150	2	7,86	58600
DSC500H120/6	6000	500	430250	2	7,86	58600
DSC600H120/3	3000	600	430160	2	8,11	70600
DSC600H120/6	6000	600	430260	2	8,11	70600