


## DST...H120 Cable Ladder

### Overview:

#### Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E**- stainless steel (SS)  
**L**- powder coating in a full range of colours (PC)

#### IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
  - cable ladder from 2 to 12m long
  - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps  
**UK**

### Versions:

Sheet thickness: **3,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DST200H120/6	6000	200	430420	2	10,25	22600
DST300H120/6	6000	300	430430	2	10,39	34600
DST400H120/6	6000	400	430440	2	10,88	46600
DST500H120/6	6000	500	430450	2	11,16	58600
DST600H120/6	6000	600	430460	2	11,41	70600