


## DSP...H150 Cable Ladder

### Overview:

#### Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E**- stainless steel (SS)  
**L**- powder coating in a full range of colours (PC)

#### IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
  - cable ladder from 2 to 12m long
  - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps  
**UK**

### Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSP200H150/3	3000	200	431723	1	6,84	27800
DSP200H150/6	6000	200	431826	1	6,84	27800
DSP300H150/3	3000	300	431733	1	7,12	37600
DSP300H150/6	6000	300	431836	1	7,12	37600
DSP400H150/3	3000	400	431743	1	7,41	50700
DSP400H150/6	6000	400	431846	1	7,41	50700
DSP500H150/3	3000	500	431753	1	7,70	63900
DSP500H150/6	6000	500	431856	1	7,70	63900
DSP600H150/3	3000	600	431763	1	7,99	87800
DSP600H150/6	6000	600	431866	1	7,99	87800