


DSC...H150 Cable Ladder

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
 - cable ladder from 2 to 12m long
 - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps
UK

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSC200H150/3	3000	200	431720	1	8,65	27800
DSC200H150/6	6000	200	431820	1	8,65	27800
DSC300H150/3	3000	300	431730	1	8,79	37600
DSC300H150/6	6000	300	431830	1	8,79	37600
DSC400H150/3	3000	400	431740	1	9,28	50700
DSC400H150/6	6000	400	431840	1	9,28	50700
DSC500H150/3	3000	500	431750	1	9,56	63900
DSC500H150/6	6000	500	431850	1	9,56	63900
DSC600H150/3	3000	600	431760	1	9,81	87800
DSC600H150/6	6000	600	431860	1	9,81	87800