


## DST...H150 Cable Ladder

### Overview:

#### Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E**- stainless steel (SS)  
**L**- powder coating in a full range of colours (PC)

#### IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
  - cable ladder from 2 to 12m long
  - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps  
**UK**

### Versions:

Sheet thickness: **3,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DST200H150/6	6000	200	432020	1	12,85	27800
DST300H150/6	6000	300	432030	1	12,99	37600
DST400H150/6	6000	400	432040	1	13,48	50700
DST500H150/6	6000	500	432050	1	13,76	63900
DST600H150/6	6000	600	432060	1	14,01	87800