


## DSP...H200 Cable Ladder

### Overview:

#### Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 8m.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
E- stainless steel (SS)  
L- powder coating in a full range of colours (PC)

#### IMPORTANT!

In case of large quantity orders available are:

- cable ladders with slotted side walls
  - cable ladder from 2 to 12m long
  - cable ladders of 1.2, 2.5mm steel thickness of a side wall
- Cable ladder with rungs adapted for use with Cable Clamps  
UK

### Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DSP200H200/3	3000	200	433323	1	8,04	37800
DSP200H200/6	6000	200	433426	1	8,04	37800
DSP300H200/3	3000	300	433333	1	8,32	57800
DSP300H200/6	6000	300	433436	1	8,32	57800
DSP400H200/3	3000	400	433343	1	8,61	77800
DSP400H200/6	6000	400	433446	1	8,61	77800
DSP500H200/3	3000	500	433353	1	8,90	97800
DSP500H200/6	6000	500	433456	1	8,90	97800
DSP600H200/3	3000	600	433363	1	9,19	117800
DSP600H200/6	6000	600	433466	1	9,19	117800