


KBD...H60 Cable Tray

Overview:

Application
Cable routing



Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

Important!
Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBP... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile). Available when ordering in large quantity are 6m long tray sections. To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

Versions:

Sheet thickness: 1,2 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBD50H60/3	3000	50	162324	12	2,02	2900
KBD100H60/3	3000	100	162410	6	2,50	5800
KBD150H60/3	3000	150	162415	6	3,00	8800
KBD200H60/3	3000	200	162420	4	3,50	11800
KBD300H60/3	3000	300	162430	4	4,50	17800
KBD400H60/3	3000	400	161840	4	5,50	23800
KBD500H60/3	3000	500	161850	2	6,50	29800
KBD600H60/3	3000	600	161860	2	7,50	35800

Connected products:

