

KKBL...H30 90° Horizontal Bend

Overview:

Application

Diversions in cable routing.

Material



Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



**For installation use Screw Sets SGK M6×10 or SG M6×10.
In case of special orders please specify dimensions a and b.**

Versions:

Sheet thickness: **0,7 mm**

| Symbol | Width a [mm] | Catalogue number | Quantity in box | Weight 1 pc. |
|-------------------|--------------|------------------|-----------------|--------------|
| KKBL50H30 | 50 | 135005 | 20 | 0,10 |
| KKBL100H30 | 100 | 135010 | 20 | 0,18 |
| KKBL150H30 | 150 | 135015 | 10 | 0,29 |
| KKBL200H30 | 200 | 135020 | 10 | 0,42 |
| KKBL300H30 | 300 | 135030 | 10 | 0,82 |

Connected products:



KJ...H30 Cable Tray



KGR...H30 Cable Tray



KGL...H30 Cable Tray



KBJ...H30 Cable Tray



KBR...H30 Cable Tray