

KFJ...H60 Cable Tray

Overview:

Planned production start in 2nd quarter of 2014



APPLICATIONS

Cable routing

MATERIAL

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG).

Connection of a click system. In order to provide stable electric continuity connection 1 set of screws SGM6x12 or SGM6x12 should be used. Information about Covers for Cable Trays and Covers for Fittings

New click connection system of cable trays

Advantages of new system:

- Fast and easy assembly
- Firm click connection
- Deep stamping around the slots in the bottom increase the strenght
- dense perforation with stamping around the slots for excellent heat transfer
- designed to enable cable tray installation on supports from BAKS anywhere within the system
- slotted holes Ø11 in the cable tray bottom allow for suspension on a threaded rod

Applications of Cable Trays KF...

- In electric installation assembled on grounded steel structures
- In electrical installations with safe tension
- In hydraulic, pneumatic installations etc...

Versions:

Sheet thickness: **1,0 mm**

| Symbol | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Weight [1m] | Effective section |
|-------------|--------------|--------------|------------------|-----------------|-------------|-------------------|
| KFJ50H60/3 | 3000 | 50 | 162523 | 4 | 1,25 | 2900 |
| KFJ100H60/3 | 3000 | 100 | 162623 | 4 | 1,53 | 5800 |
| KFJ150H60/3 | 3000 | 150 | 162723 | 4 | 1,86 | 8800 |
| KFJ200H60/3 | 3000 | 200 | 162823 | 4 | 2,13 | 11800 |
| KFJ300H60/3 | 3000 | 300 | 162923 | 4 | 2,96 | 17800 |
| KFJ400H60/3 | 3000 | 400 | 163023 | 2 | 3,37 | 23800 |
| KFJ500H60/3 | 3000 | 500 | 163123 | 2 | 4,04 | 29800 |
| KFJ600H60/3 | 3000 | 600 | 163223 | 2 | 4,64 | 35800 |