

PZKZWP... Cover with lock

Overview:

APPLICATIONS

Protecting cables against damage.
Tight cover protection against accumulation of dirt and dust.



MATERIAL

Steel, hot-dip galv.
to PN-EN ISO 1461:2011 (HDG)
Available finishes:
E - stainless steel (SS), grade 1.4301 (AISI304)
L - powder coating in a full range of colours (PC)

PZKZWP
ŠÍRKY: 50 a 100 mm
- 1 SYMETRICKÝ ZAMOK
ŠÍRKY NAD: 100 mm
- 2 ZAMKY

NOTE:

In every cover are pre-punched holes, necessary for dipping-in melted zinc (ref. hot-dip galvanizing process)
Covers fit trays KZW... and KZLW...

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
PZKZWP50/2	2000	50	308505	20	0,86
PZKZWP50/3	3000	50	308605	20	0,86
PZKZWP100/2	2000	100	308510	10	1,48
PZKZWP100/3	3000	100	308610	10	1,48
PZKZWP200/2	2000	200	308520	6	2,71
PZKZWP200/3	3000	200	308620	6	2,71
PZKZWP300/2	2000	300	308530	6	3,95
PZKZWP300/3	3000	300	308630	6	3,95
PZKZWP400/2	2000	400	308540	4	5,19
PZKZWP400/3	3000	400	308640	4	5,19
PZKZWP500/2	2000	500	308550	6	6,42
PZKZWP500/3	3000	500	308650	4	6,42
PZKZWP600/2	2000	600	308560	4	7,66
PZKZWP600/3	3000	600	308660	4	7,66