


PZKZWC Cover with lock

Overview:

APPLICATIONS

Protecting cables against damage.
Tight cover protection against accumulation of dirt and dust.



MATERIAL

Steel, hot-dip galv.
to PN-EN ISO 1461:2011 (HDG)
Available finishes:
E - stainless steel (SS), grade 1.4301 (AISI304)
L - powder coating in a full range of colours (PC)

PZKZWC
ŠÍRKY: 50 a 100 mm
- 1 SYMETRICKÝ ZAMOK
ŠÍRKY NAD: 100 mm
- 2 ZAMKY

NOTE:

In every cover are pre-punched holes, necessary for dipping-in melted zinc (ref. hot-dip galvanizing process)
Covers fit trays KZW... and KZLW...

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
PZKZWC50/2	2000	50	308705	10	1,15
PZKZWC50/3	3000	50	308805	10	1,15
PZKZWC100/2	2000	100	308710	6	1,97
PZKZWC100/3	3000	100	308810	6	1,97
PZKZWC200/2	2000	200	308720	4	3,62
PZKZWC200/3	3000	200	308820	4	3,62
PZKZWC300/2	2000	300	308730	4	5,27
PZKZWC300/3	3000	300	308830	4	5,27
PZKZWC400/2	2000	400	308740	2	6,92
PZKZWC400/3	3000	400	308840	2	6,92
PZKZWC500/2	2000	500	308750	2	8,56
PZKZWC500/3	3000	500	308850	2	8,56
PZKZWC600/2	2000	600	308760	2	10,21
PZKZWC600/3	3000	600	308860	2	10,21