


DGOD...H60F Cable Ladder

Overview:

APPLICATION
Cable routing

MATERIAL
Steel, hot-dip galvanised
to PN-EN ISO 1461:2011 (HDG)
Available finishes:
L- powder coating in a full range of colours (PC)



- For assembly use 2 pcs of Straight connectors LDC/LDOCH60 and 8 sets of screw SGKM8x14
- For vertical direction change use 2 pcs of Articulated Connector LGC/LGOCH60 and 8 sets of screw SGKM8x14
- For horizontal direction change use 2 pcs of Angle Connector LKD/LKDOCH60 and 8 sets of screw SGKM8x14

Max. safe load: 20 kg/m
Max. spacing of supports: 1.5m

Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DGOD100H60/3F	3000	100	867510	2	2,01
DGOD100H60/6F	6000	100	867511	2	2,01
DGOD200H60/3F	3000	200	867520	2	2,24
DGOD200H60/6F	6000	200	867521	2	2,24
DGOD300H60/3F	3000	300	867530	2	2,47
DGOD300H60/6F	6000	300	867531	2	2,47
DGOD400H60/3F	3000	400	867540	2	2,81
DGOD400H60/6F	6000	400	867541	2	2,81