

## PGM Threaded Rod

### Overview:

**APPLICATIONS**  
Suspending cable runs.

**MATERIAL**  
Electro-galvanised steel (EG)  
Available finishes:  
E- Stainless steel, grade 1.4401 (A4)



### STEEL GRADE 5.8

### Versions:

Symbol	Length L [m]	Catalogue number	Quantity in box	Weight 1 pc.	Thread M [mm]	Tensile strength [KN]
<b>PGM 8/01</b>	<b>100</b>	<b>650501</b>	<b>100</b>	<b>0,03</b>	<b>8</b>	<b>19</b>
<b>PGM 8/02</b>	<b>200</b>	<b>650601</b>	<b>100</b>	<b>0,06</b>	<b>8</b>	<b>19</b>
<b>PGM 8/03</b>	<b>300</b>	<b>650701</b>	<b>50</b>	<b>0,09</b>	<b>8</b>	<b>19</b>
<b>PGM 8/ 1</b>	<b>1000</b>	<b>650801</b>	<b>50</b>	<b>0,32</b>	<b>8</b>	<b>19</b>
<b>PGM 8/ 2</b>	<b>2000</b>	<b>650901</b>	<b>25</b>	<b>0,64</b>	<b>8</b>	<b>19</b>
<b>PGM 8/ 3</b>	<b>3000</b>	<b>651501</b>	<b>25</b>	<b>0,96</b>	<b>8</b>	<b>19</b>
<b>PGM10/ 1</b>	<b>1000</b>	<b>651001</b>	<b>25</b>	<b>0,49</b>	<b>10</b>	<b>30</b>
<b>PGM10/ 2</b>	<b>2000</b>	<b>651101</b>	<b>25</b>	<b>1,00</b>	<b>10</b>	<b>30</b>
<b>PGM10/ 3</b>	<b>3000</b>	<b>651601</b>	<b>25</b>	<b>1,50</b>	<b>10</b>	<b>30</b>