

PZLZZMCH50 Cover For 45° Vertical Bend - External H50

Overview:

APPLICATION

Protecting cables against damage. Tight cover protection against accumulation of dirt and dust.

Material

Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

Note:



In every cover are pre-punched holes, necessary for dipping-in melted zinc (ref. hot-dip galvanizing process)

Cover with a lock

NOTE: UP TO 50 and 100mm WIDE - 1 LOCK -

SYMMETRICALLY

OVER 100mm WIDE - 2 LOCKS



UWAGA!
DO SZEROKOŚCI 50 i 100 mm
- 1 ZAMEK SYMETRYCZNIE
POWYŻEJ 100 mm
- 2 ZAMKI

Versions:

Sheet thickness: 2,0 mm

| Symbol | Width a [mm] | Catalogue number | Quantity in box | Weight 1 pc. |
|---------------|--------------|------------------|-----------------|--------------|
| PZLZZMC50H50 | 50 | 335805 | 20 | 0,34 |
| PZLZZMC100H50 | 100 | 335810 | 20 | 0,54 |
| PZLZZMC200H50 | 200 | 335820 | 10 | 1,02 |
| PZLZZMC300H50 | 300 | 335830 | 10 | 1,80 |
| PZLZZMC400H50 | 400 | 335840 | 4 | 2,20 |
| PZLZZMC500H50 | 500 | 335850 | 4 | 2,59 |
| PZLZZMC600H50 | 600 | 335860 | 4 | 2,73 |