

KDSZH60 Wire Mesh Cable Tray

Overview:

Application
 Cable routing

Material
 Electro-galvanised steel (EG)


Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

Available from third quarter of 2013

Features & Benefits:

- Rapid assembly
- Connectors welded in the wire mesh cable tray
- Increased strenght parameters

Innovative connection of wire mesh cable trays!
 Due to high durability parameters of materials used for snap-in connectors we reach firm and sollid connection of wire mesh cable trays, equal to connection by usual bolted connectors



Versions:

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KDSZ60H60/3	3000	60	940106	8	0,55	2200
KDSZ100H60/3	3000	100	940110	8	0,79	4300
KDSZ150H60/3	3000	150	940115	8	0,85	7000
KDSZ200H60/3	3000	200	940120	4	1,09	9400
KDSZ300H60/3	3000	300	940130	4	1,76	14600
KDSZ400H60/3	3000	400	940140	2	2,14	19800
KDSZ500H60/3	3000	500	940150	2	3,09	25000
KDSZ600H60/3	3000	600	940160	2	3,56	30200