

RKPFJ...H60 Right Reducer


Overview:

Application

Cable routing width reduction.

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011.



**For the assembly use Screw Sets SGKM6x12 or SGM6x12.
In case of special orders please specify dimensions of a and b.**

Versions:

Sheet thickness: **1,0 mm**

| Symbol | Width a [mm] | Catalogue number | Quantity in box | Weight 1 pc. | Size b [mm] |
|-----------------|--------------|------------------|-----------------|--------------|-------------|
| RKPFJ100/50H60 | 100 | 165112 | 10 | 0,30 | 50 |
| RKPFJ150/100H60 | 150 | 165212 | 10 | 0,37 | 100 |
| RKPFJ200/100H60 | 200 | 165312 | 10 | 0,43 | 100 |
| RKPFJ200/150H60 | 200 | 165412 | 10 | 0,45 | 150 |
| RKPFJ300/200H60 | 300 | 165512 | 10 | 0,58 | 200 |
| RKPFJ400/300H60 | 400 | 165530 | 10 | 0,73 | 300 |
| RKPFJ500/400H60 | 500 | 165531 | 10 | 0,89 | 400 |
| RKPFJ600/500H60 | 600 | 165532 | 10 | 0,98 | 500 |