

FLI/... - 2-16P Držiak pre vertikálne uchytenie (800-6300 A)

Overview:

Použitie

Slúži na upevnenie a zavesenie prípojnicového systému vo vertikálnej polohe.

- verzie pre 800 až 6300 A.



Symbol	Size a [mm]	Pól
FLI/2	250	2
FLI/3	292	3
FLI/4	334	4
FLI/5	376	5
FLI/6	418	6
FLI/7	460	7
FLI/8	502	8
FLI/9	544	9
FLI/10	586	10
FLI/11	628	11
FLI/12	670	12
FLI/13	712	13
FLI/14	754	14
FLI/15	796	15
FLI/16	811	16

SUPPORTED CONDUCTORS		
Fl	Al	Cu
800	20 mm	20 mm
1000	20 mm	20 mm
1200	20 mm	20 mm
1600	20 mm	16 mm
2000	20 mm	16 mm
2500	16 mm	16 mm
3200	16 mm	12 mm
4000	16 mm	12 mm
5000	12 mm	12 mm
6300	7	10 mm

Versions:

Symbol	Size a [mm]	Pól
FLI/2	250	2
FLI/3	292	3
FLI/4	334	4
FLI/5	376	5
FLI/6	418	6
FLI/7	460	7
FLI/8	502	8
FLI/9	544	9
FLI/10	586	10
FLI/11	628	11
FLI/12	670	12
FLI/13	712	13
FLI/14	754	14
FLI/15	796	15
FLI/16	811	16